

Ethernet Switch



MSH-2110



- 8 Port 10/100/1000Mbps RJ45
- 2 Slot 1Gbps SFP

MSH-2116



- 16 Port 10/100/1000Mbps RJ45

MSH-2120



- 16 Port 10/100/1000Mbps RJ45
- 4 Slot 1Gbps

MSH-2026E



- 24 Port 10/100/1000Mbps RJ45
- 2 Slot 1Gbps SFP, 2 Port 10/100/1000Mbps Combo

MSH-2128



- 24 Port 10/100/1000Mbps RJ45
- 4 Slot 1Gbps SFP

MSH-2128T



- 24 Port 10/100/1000Mbps RJ45

MSH-2128F



- 16 Port 10/100/1000Mbps RJ45
- 12 Slot 1Gbps SFP

MSH-2152



- 48 Port 10/100/1000Mbps RJ45
- 4 Slot 1Gbps SFP

MSH-2127F



- 24 Slot 1Gbps SFP
- 2 Slot 1Gbps or 2.5Gbps SFP
- 1 Port 10/100/1000Mbps RJ45

MSH-3128



- 24 Port 10/100/1000Mbps RJ45
- 4 Slot 10Gbps or 1Gbps SFP+

MSH-3152



- 48 Port 10/100/1000Mbps RJ45
- 4 Slot 10Gbps or 1Gbps SFP+

MSH-3128F



- 24 Slot 1Gbps SFP
- 8 Port 10/100/1000Mbps Combo
- 4 Slot 10Gbps or 1Gbps SFP+

MHM-2204



- 4 Port 10/100/1000Mbps RJ45
- 2 Slot 1Gbps or 2.5Gbps SFP

MHM-2208



- 8 Port 10/100/1000Mbps RJ45
- 2 Slot 1Gbps or 2.5Gbps SFP

MHM-2408



- 8 Port 10/100/1000Mbps RJ45
- 2 Slot 1Gbps or 2.5Gbps SFP
- 2 Slot 1Gbps SFP

MHM-2208P



- 8 Port 10/100/1000Mbps, PoE
- 2 Slot 1Gbps or 2.5Gbps SFP

MHM-2408P



- 8 Port 10/100/1000Mbps, PoE
- 2 Slot 1Gbps or 2.5Gbps SFP
- 2 Slot 1Gbps SFP

MHM-2208-BP



- 8 Port 10/100/1000Mbps RJ45
- 2 Slot 1Gbps or 2.5Gbps SFP
- Optical Bypass Switch

MHM-2408-BP



- 8 Port 10/100/1000Mbps RJ45
- 2 Slot 1Gbps or 2.5Gbps SFP
- 2 Slot 1Gbps SFP
- Optical Bypass Switch

MHM-2408-R



- 16 Port 10/100/1000Mbps RJ45
- 4 Slot 1Gbps or 2.5Gbps SFP
- 4 Slot 1Gbps SFP

MHM-2126



- 24 Port 10/100/1000Mbps RJ45
- 2 Slot 1Gbps or 2.5Gbps SFP

MHM-2126P



- 24 Port 10/100/1000Mbps, PoE
- 2 Slot 1Gbps or 2.5Gbps SFP

MHM-2129F



- 24 Slot 1Gbps SFP
- 4 Slot 10Gbps SFP+
- 1 Port 10/100/1000Mbps, Mgmt

MHM-2227F



- 16 Slot 1Gbps SFP
- 8 Slot 1Gbps or 2.5Gbps SFP
- 2 Slot 10Gbps SFP+
- 1 Port 10/100/1000Mbps, Mgmt

MP-2401



- DC 24V 1.0A Power Supply for Industrial Switch

Common Spec.

- ITU-T G.8032 ERPS(Ethernet Ring Protection Switching)
- Power Redundancy
- Operating temp.: -40°C ~ 80°C